

		8		7		6		5		4		3		2		1															
F																F															
E																E															
D																D															
C																C															
B		技术要求: 1. 产品表面无缩水、披锋、油污、缺胶、杂色等不良现象; 2. 产品符合ROHS环保标准。														B															
A		<table><tr><td colspan="2">未注公差尺寸按 GB/T 1804-2016</td><td colspan="2" rowspan="6">乐清市地宏接插件有限公司</td><td colspan="2" rowspan="6">设计: 黄银丹 审核: 黄银丹</td><td colspan="2" rowspan="6">材料: 重量/克 视图: 比例:</td><td colspan="2" rowspan="6">系列: 针座系列 编号: MX34036UF2 品名: DJ7361-0.7-10A</td></tr><tr><td>F</td><td>偏差值</td></tr><tr><td>>0.5~6</td><td>±0.05</td></tr><tr><td>>6~30</td><td>±0.1</td></tr><tr><td>>30~120</td><td>±0.15</td></tr><tr><td>>120~400</td><td>±0.2</td></tr></table>		未注公差尺寸按 GB/T 1804-2016		 乐清市地宏接插件有限公司		设计: 黄银丹 审核: 黄银丹		材料: 重量/克 视图:  比例:		系列: 针座系列 编号: MX34036UF2 品名: DJ7361-0.7-10A		F	偏差值	>0.5~6	±0.05	>6~30	±0.1	>30~120	±0.15	>120~400	±0.2							A	
未注公差尺寸按 GB/T 1804-2016		 乐清市地宏接插件有限公司		设计: 黄银丹 审核: 黄银丹										材料: 重量/克 视图:  比例:		系列: 针座系列 编号: MX34036UF2 品名: DJ7361-0.7-10A															
F	偏差值																														
>0.5~6	±0.05																														
>6~30	±0.1																														
>30~120	±0.15																														
>120~400	±0.2																														
		8		7		6		5		4		3		2		1															